

Model		LOGAN								
Types		KL 3	KL 4 KL 4F	KL 5 KL 5F	KL 6 KL 6F	KL 7 KL 7F	KL 8 KL 8F	KL 9 KL 9F	KL 10 KL 10F	
Description of boiler		Manually stocked, cast iron sectional boilers, for solid fuels in 3pass flue circulation principle								
Number of sections	pcs.	3	4	5	6	7	8	9	10	
Output range	(Coal) kW	16-20	22-30	32-40	42-50	52-60	62-70	72-80	82-90	
	(Wood) kW	14-16	18-24	26-32	34-40	42-48	50-56	60-66	70-76	
	(Pellet) kW	18	26	34	42	50				
Water Content	lt	27.5	34	41	47.5	54	60.5	66.5	73	
Combustion chamber		Height 485 mm X Width 360 mm								
Max. logwood length	mm	200	300	400	500	600	700	800	900	
Max. fuel loading height	mm	425								
Temperature control range	°C	50 - 90								
Max. operating temperature	°C	100								
Max. operating pressure	bar	4								
Water flow/return (F / R)	G	1 ½"								
Filling / draining (FD)	G	½"								
External dimensions	L	mm	610	710	810	910	1010	1110	1210	1310
	L2	mm	400	500	600	700	800	900	1000	1100
	Flue outlet (D)	mm	160				175			

