

Model		KAPPA							
Types		KP 3	KP 4	KP 5	KP 6	KP 7	KP 8	KP 9	KP 10
			KP 4F	KP 5F	KP 6F	KP 7F	KP 8F	KP 9F	KP 10F
Description of boiler		Manually stocked, cast iron sectional boilers, for solid fuels in 2pass flue circulation principle							
Number of sections	pcs.	3	4	5	6	7	8	9	10
Output range	(Coal) kW	15-18	22-26	28-32	34-38	40-46	48-54	56-62	64-70
	(Wood) kW	12-14	18-22	24-28	30-34	36-42	44-48	50-56	58-64
	(Pellet) kW		24	32	38	45			
Water Content	lt	22	27.5	33.5	39.5	45.5	51.5	57.5	63.5
Combustion chamber		Height 425 mm X Width 315 mm							
Max. logwood length	mm	200	300	400	500	600	700	800	900
Fuel loading clearance	mmxmm	330 x 324							
Max. fuel loading height	mm	375							
Temperature control range	°C	50 - 90							
Max. operating temperature	°C	100							
Max. operating pressure	bar	4							
Water flow/return (F / R)	R	1 ½"							
Filling / draining (FD)	R	½"							
External dimensions	L	525	625	725	825	925	1025	1125	1225
	L2	380	480	580	680	780	880	980	1080
	Flue outlet (D)	160							175

