

Model		PUNTO 8	
Fuel parameters		Wood pellets size 6 mm EnPlus A1 or A2 to ISO 17725-2	
Rated heat input (maximum power)		8,3	
Nominal heat output	kW	7,2	
Efficiency at nominal heat output	%	87,2	
Fuel consumption at nominal heat output	kg/h	1,76	
CO content (13% O ₂) at nominal heat output	%	0,01	
	mg/m ³	126	
Flue temperature at nominal heat output	°C	166	
Mass flow in flue at nominal heat output	gr/s	6,8	
Requested draught at chimney	Pa	12	
Reduced heat output	kW	3,6	
Efficiency at reduced heat output	%	90,9	
Fuel consumption at reduced heat output	kg/h	0,83	
CO content (13% O ₂) at reduced heat output	%	0.006	
	mg/m ³	92	
Flue temperature at nominal heat output	°C	99	
Mass flow in flue at reduced heat output	gr/s	4,4	
Requested draught at chimney	Pa	10	
Autonomy (nominal - reduced heat output)	h	8 - 16	
Maximum power rating	W	316	
Power rating at work	W	94	
Supply voltage and frequency	V/Hz	230/50	
Fuel tank capacity	kg / lt	14 / 20	
Weight	kg	95	
External dimensions	HxWxL	mm	928 x 430 x 550
	Flue outlet diameter	mm	Ø 80
	Ducting outlet (optional)	mm	Ø 80

